OSEE Mega 15S4

Multi-Window Production Monitor, 15.4-Inch – Manufacturer Specifications



Tech Specs

Display	15.4-inch IPS Black LCD; 1920 × 1200; RGB 10-bit; 178° H/V.
Brightness & Contrast	1500 nits; 1650:1 contrast ratio.
Screen Surface	Low-reflection AR film; Rd 0.15%.
Color Space	Rec.709.
Color Processing	Color-Fidelity V2; 22-bit processing; tetrahedral 3D-LUT interpolation.
Custom LUTs	10 user LUTs; up to 65 × 65 × 65.
Display Calibration	USB-C with X-Rite i1 Display Pro; no computer required. Probe sold separately.
Multi-Window Viewing	Select up to 4 windows from 6 inputs; landscape or portrait orientation.
MySets	8 MySets; up to 8 monitoring tools per set.
HDMI Inputs	3 × HDMI 2.0 (Type-A); up to 4096 × 2160p60.
SDI Inputs	3 × 3G-SDI (BNC); up to 2048 × 1080p60.
Video Outputs	1 × HDMI 1.4 (Type-A); 1 × 3G-SDI (BNC).
USB & Audio	1 × USB-A; 1 × USB-C; 3.5 mm headphone output; built-in speaker.
Power	AC 100–240 V, 50/60 Hz; DC 11–17 V/5 A via 4-pin XLR; 45 W max; V-Mount/Gold Mount.
Mounting	VESA 100 × 100 mm; cheese plate with 1/4-inch and 3/8-inch threads; top handle.
Dimensions & Weight	14.53 × 3.35 × 10.43 in (36.9 × 8.5 × 26.5 cm); 10.14 lb (4.6 kg), monitor only.

What's in the box

- Mega 15S4 Monitor
- Portable Travel Case (Sun Hood)
- VESA Adapter
- Battery Plates (V&AB Mount)
- Cheese Plate

Source: OSEE official product page – https://osee-tech.com/products/osee-mega-15s4 ("Tech Specs" and "What's in the box"), retrieved 15 Nov 2026. Specification text reproduced as published by the manufacturer; OSEE does not publish a separate PDF datasheet for this model. Compiled by Videoset.

מקור: דף המוצר הרשמי של OSEE. המפרט מועתק כפי שפורסם על ידי היצרן; היצרן אינו מפרסם קובץ PDF נפרד לדגם זה.