USB Video Capture Adapter Cable - S-Video/Composite to USB 2.0 SD Video Capture Device Cable - TWAIN Support - Analog to Digital Converter for Media Storage - Windows Only

Product ID: SVID2USB232



ThisUSB video capture adapteroffers an easy to useanalog video capturesolution, enabling you to convertvideo(and accompanying audio) from acomposite or S Videosource to your Windows-based computer.

An easy-to-use device for recordinganalog videoto your PC from external sources, such as aVCRor camcorder, theS Video and composite to USB converteroffers the perfect solution for Betamax orVHS video capture, with real-time MPEG-1, MPEG-2, and MPEG-4 encoding.

Thisanalog to digital video adapteris ideal for convertingVHSor home movies todigitalformat, as well as importing videos onto your Windows computer for editing.It also features a snapshot function that enables users to capture still images from theiranalog video.

Thisanalog video capture cabledeliversseamlessanalog video capturefor yourWindows devices. As well, theS Video / composite to USB adapterhas TWAIN support, to ensure compatibility with a wide range of systems and software.

Thisanalog to digital converter cableconnects to your PC throughUSB 2.0and is compact enough to fit in the palm of your hand, providing a conveniently portablevideo capturesolution that's more than suitable for use with laptops and desktop computers alike.

SVID2USB232is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Note: Thisconverter is for use with Windows-based devices only and is not compatible with macOS.

Certifications, Reports and Compatibility



Applications

• Digitally record and view content from your reliable legacy equipment

• Convert your VHS home movies to digital format

• Connect your VCR or other analog source to your PC and capture audio/video in MPEG 1/2/4 format

Features

• SD VIDEO CAPTURE: USB video capture adapter converts composite/S-Video & RCA 2ch audio into digital media; supports 30fps @720x480i (NTSC)/25fps @720x576 (PAL/SECAM) & MPEG-1/MPEG-2/MPEG-4 encoding

• SOFTWARE COMPATIBILITY: USB 2.0 video capture cable drivers are TWAIN compatible for use w/ third-party software; incl. software provides an out of the box solution for Windows (7-10) computers

• CAPTURE & SHARE: Using third-party software (OBS, etc.) you can capture standard def 480i video and stream on services like YouTube (or other social media platforms) or in training & resource centers

• PORTABLE DESIGN: USB bus-powered USB video capture device is compact & lightweight, so you can easily take it from your media room or classroom while in the office, working from home or on the go

• ANALOG TO DIGITAL VIDEO CONVERTER: Use the intuitive Windows software (included) to easily capture video from your VCR/BETA, camcorder or home videos VHS to Digital/DVD or PC storage

General		
	UPC	065030875547
	Package Quantity	1
	Warranty	2 Years
Special Notes / Requirements		
	Special Notes	This converter is for use with Windows-based devices only and is not compatible with macOS
Power		
	Input Voltage	5V DC
	Output Voltage	5 DC

Physical & Environmental		
	Color	Black
	Material	Plastic
	Cable Length	10.2 in [26 cm]
	Product Length	3.9 in [100.0 mm]
	Product Width	1.4 in [35.0 mm]
	Product Height	0.6 in [14.0 mm]
	Weight of Product	2.3 oz [64 g]
	Operating Temperature	0C to 50C (32F to 122F)
	Storage Temperature	-20C to 60C (-4F to 140F)
	Humidity	5~85% RH Non-condensing
Performance		
	Maximum Data Transfer Rate	480Mbps
	Maximum Analog Resolutions	720x480(NTSC) / 720x576(PAL)
Hardware		
	AV Input	Audio RCA
		Composite
		S-Video
	AV Output	USB
	Audio	Yes
	Interface	USB 2.0
	Industry Standards	NTSC, PAL, SECAM
		Video Encoding: MPEG 1, MPEG 2, and MPEG 4
		DirectShow Compatible
	Chipset ID	EM28281

Packaging & In-the-Box		
	Included in Package	1 - USB 2.0 Capture Device
		1 - User Guide
		1 - Driver CD
	Package Width	8.2 in [20.8 cm]
	Package Depth	5.9 in [15 cm]
	Package Height	1.4 in [36 mm]
	Shipping (Package) Weight	6.1 oz [174 g]

Connector(s)		
	Connector 1 (Quantity)	1
	Connector 1	USB-A (480Mbps, 2.5W)
	Connector 2 (Quantity)	1
	Connector 2	S-Video (Y/C)
	Connector 3 (Quantity)	1
	Connector 3	RCA (Composite Video)
	Connector 4 (Quantity)	1
	Connector 4	RCA (Stereo Audio)

Product appearance and specifications are subject to change without notice.